

Package: RcppGetconf (via r-universe)

July 16, 2024

Type Package

Title 'Rcpp' Interface for Querying System Configuration Variables

Version 0.0.3.1

Date 2018-11-16

Author Dirk Eddelbuettel

Maintainer Dirk Eddelbuettel <edd@debian.org>

Description The 'getconf' command-line tool provided by 'libc' allows querying of a large number of system variables. This package provides similar functionality.

URL <https://github.com/eddelbuettel/rcppgetconf>,
<https://dirk.eddelbuettel.com/code/rcpp.getconf.html>

BugReports <https://github.com/eddelbuettel/rcppgetconf/issues>

Imports Rcpp

LinkingTo Rcpp

SystemRequirements A POSIX system. Currently Linux and OS X are known to work.

OS_type unix

License GPL (>= 2)

Encoding UTF-8

RoxygenNote 6.0.1

Repository <https://eddelbuettel.r-universe.dev>

RemoteUrl <https://github.com/eddelbuettel/rcppgetconf>

RemoteRef HEAD

RemoteSha 8fe516ac7097945ae363e2002c85ad694e44ce05

Contents

getAll	2
getConfig	3

Index	4
--------------	----------

getAll	<i>Return all System Configuration Settings</i>
--------	---

Description

Retrieve all configuration settings

Usage

```
getAll(path = ".")
```

Arguments

path An optional character object specifying a path. Default is the current directory.

Details

This functions returns all configuration settings which can be queried in a data.frame object. The system-level functions `sysconf`, `pathconf` and `confstr` provide all the underlying information.

Value

A data.frame with three colums for key, value and (source) type. Not all keys return a value; in those cases an empty string is returned. Type is one of path, sys and conf and signals how the value was obtained.

Author(s)

Dirk Eddelbuettel

See Also

[getConfig](#)

Examples

```
if (Sys.info()[["sysname"]] != "SunOS") {  
  head(getAll(), 30)  
  subset(getAll(), type=="path")  
}
```

getConfig	<i>Return a System Configuration Setting</i>
-----------	--

Description

Retrieve one configuration setting

Usage

```
getConfig(var, path = ".")
```

Arguments

var	An character object specifying a value for which configuration is queried.
path	An optional character object specifying a path. Default is the current directory.

Details

This functions returns the configuration setting for a given input. in a data.frame object. The system-level functions `sysconf`, `pathconf` and `confstr` provide the underlying information.

Value

A result value corresponding to the requested setting. The return type can be either integer for a numeric value, character for text or NULL in case to value could be retrieved.

Author(s)

Dirk Eddelbuettel

See Also

[getAll](#)

Examples

```
if (Sys.info()[["sysname"]] != "SunOS") {
  getConfig("_NPROCESSORS_CONF") # number of processor
  getConfig("LEVEL1_ICACHE_SIZE") # leve1 cache size
  getConfig("GNU_LIBC_VERSION") # libc version
}
```

Index

`getAll`, [2](#), [3](#)
`getConfig`, [2](#), [3](#)