

# Package: RcppMsgPack (via r-universe)

August 9, 2024

**Type** Package

**Title** 'MsgPack' C++ Header Files and Interface Functions for R

**Version** 0.2.3.2

**Date** 2023-04-10

**Author** Travers Ching and Dirk Eddelbuettel; the authors and contributors of MsgPack

**Maintainer** Dirk Eddelbuettel <edd@debian.org>

**Description** 'MsgPack' header files are provided for use by R packages, along with the ability to access, create and alter 'MsgPack' objects directly from R. 'MsgPack' is an efficient binary serialization format. It lets you exchange data among multiple languages like 'JSON' but it is faster and smaller. Small integers are encoded into a single byte, and typical short strings require only one extra byte in addition to the strings themselves. This package provides headers from the 'msgpack-c' implementation for C and C++(11) for use by R, particularly 'Rcpp'. The included 'msgpack-c' headers are licensed under the Boost Software License (Version 1.0); the code added by this package as well the R integration are licensed under the GPL (>= 2). See the files 'COPYRIGHTS' and 'AUTHORS' for a full list of copyright holders and contributors to 'msgpack-c'.

**Copyright** file inst/COPYRIGHTS

**License** GPL (>= 2)

**Imports** Rcpp

**LinkingTo** Rcpp, BH

**URL** <https://github.com/eddelbuettel/rcppmsgpack>,  
<https://dirk.eddelbuettel.com/code/rcpp.msgpack.html>

**BugReports** <https://github.com/eddelbuettel/rcppmsgpack/issues>

**RoxygenNote** 6.0.1

**Suggests** knitr, rmarkdown, microbenchmark

**VignetteBuilder** knitr  
**Repository** <https://eddelbuettel.r-universe.dev>  
**RemoteUrl** <https://github.com/eddelbuettel/rcppmsgpack>  
**RemoteRef** HEAD  
**RemoteSha** 857afb9c5bb28e4929910b08a9b89238ec1bb0f0

Contents

RcppMsgPack-package . . . . .	2
arrayEx . . . . .	3
enumEx . . . . .	3
msgpack_format . . . . .	4
msgpack_map . . . . .	4
msgpack_pack . . . . .	5
msgpack_read . . . . .	6
msgpack_simplify . . . . .	6
msgpack_timestamp_decode . . . . .	7
msgpack_timestamp_encode . . . . .	8
msgpack_unpack . . . . .	8
msgpack_write . . . . .	9
<b>Index</b>	<b>11</b>

---

RcppMsgPack-package	<i>'MsgPack' C++ Header Files and Interface Functions for R</i>
---------------------	---

---

Description

'MsgPack' header files are provided for use by R packages, along with the ability to access, create and alter 'MsgPack' objects directly from R. 'MsgPack' is an efficient binary serialization format. It lets you exchange data among multiple languages like 'JSON' but it is faster and smaller. Small integers are encoded into a single byte, and typical short strings require only one extra byte in addition to the strings themselves. This package provides headers from the 'msgpack-c' implementation for C and C++(11) for use by R, particularly 'Rcpp'. The included 'msgpack-c' headers are licensed under the Boost Software License (Version 1.0); the code added by this package as well the R integration are licensed under the GPL (>= 2). See the files 'COPYRIGHTS' and 'AUTHORS' for a full list of copyright holders and contributors to 'msgpack-c'.

Package Content

Index: This package was not yet installed at build time.

Maintainer

Dirk Eddelbuettel <edd@debian.org>

**Author(s)**

Travers Ching and Dirk Eddelbuettel; the authors and contributors of MsgPack

---

arrayEx

*Simple MsgPack Example*

---

**Description**

Simple MsgPack Example

**Usage**

arrayEx()

**Details**

The function provides a simple illustration of MessagePack.

**Value**

A boolean value of TRUE is returned, but the function exists for its side effect.

**See Also**

The MessagePack documentation, particularly the msgpack-c examples.

---

enumEx

*Second simple MsgPack Example*

---

**Description**

Second simple MsgPack Example

**Usage**

enumEx()

**Details**

The function provides a simple illustration of MessagePack.

**Value**

A boolean value of TRUE is returned, but the function exists for its side effect.

**See Also**

The MessagePack documentation, particularly the msgpack-c examples.

---

msgpack_format	<i>Format data for 'MsgPack'</i>
----------------	----------------------------------

---

### Description

A helper function to format R data for input to 'MsgPack'.

### Usage

```
msgpack_format(x)
```

```
msgpackFormat(x)
```

### Arguments

**x**                      An r object.

### Value

A formatted R object to use as input to msgpack\_pack. Vectors are converted into Lists.

### Examples

```
x <- msgpack_format(1:10)
x_packed <- msgpack_pack(x)
x_unpacked <- msgpack_unpack(x_packed)
x_simplified <- msgpack_simplify(x_unpacked)
```

---

msgpack_map	<i>'MsgPack' Map</i>
-------------	----------------------

---

### Description

A helper function to create a map object for input to 'MsgPack'.

### Usage

```
msgpack_map(key, value)
```

```
msgpackMap(key, value)
```

### Arguments

**key**                      A list or vector of keys (coerced to list). Duplicate keys are fine (connects to std::multimap in C++).

**value**                    A list or vector of values (coerced to list). This should be the same length as key.

**Value**

An data.frame also of class "map" that can be used as input to msgpack\_pack.

**Examples**

```
x <- msgpack_map(key=letters[1:10], value=1:10)
x_packed <- msgpack_pack(x)
x_unpacked <- msgpack_unpack(x_packed)
```

---

msgpack_pack	<i>'MsgPack' Pack</i>
--------------	-----------------------

---

**Description**

Serialize any number of objects into a single message. Unnamed List is converted into Array, Map/Data.frame and Named Lists are converted into Maps. Integer, Double, Character, Raw vectors and NULL are converted into Int types (depending on size), Float types, String, Raw and Nil respectively. Raw vectors with EXT attribute are converted into Extension types. The EXT attribute should be an integer from 0 to 127.

**Usage**

```
msgpack_pack(...)

msgpackPack(...)
```

**Arguments**

... Any R objects that have corresponding msgpack types.

**Value**

A raw vector containing the message.

**See Also**

See examples/tests.r for more examples.

**Examples**

```
x <- msgpack_format(1:10)
x_packed <- msgpack_pack(x)
x_unpacked <- msgpack_unpack(x_packed)
x_simplified <- msgpack_simplify(x_unpacked)
```

---

msgpack_read	<i>'MsgPack' read</i>
--------------	-----------------------

---

### Description

A helper function to de-serialize an object read from a file or a connection.

### Usage

```
msgpack_read(file, simplify = F, mode = "auto", nbytes = 16777216)
```

```
msgpackRead(file, simplify = F, mode = "auto", nbytes = 16777216)
```

### Arguments

file	A connection, or a string describing the file or pipe to write to, depending on the mode.
simplify	Passed to msgpack_unpack. Default: FALSE.
mode	One of "auto", "file", "gzip" or "pipe". If "auto", detects based on the file string (any space == pipe, ".gz" == gzip, file otherwise). Ignored if file is a connection.
nbytes	If reading from a pipe or gzip, how many bytes to read at a time. Default: 16777216

### Examples

```
tmp <- tempfile(fileext=".gz")
msgpack_write(1:10, file=tmp)
x <- msgpack_read(tmp, simplify=TRUE)
```

---

msgpack_simplify	<i>Simplify 'MsgPack'</i>
------------------	---------------------------

---

### Description

A helper function for simplifying a 'MsgPack' return object.

### Usage

```
msgpack_simplify(x)
```

```
msgpackSimplify(x)
```

### Arguments

x	Return object from msgpack_unpack.
---	------------------------------------

**Value**

A simplified return object from msgpack\_unpack. Lists of all the same type are concatenated into an atomic vector. Maps are simplified to named lists or named vectors as appropriate. NULLs are converted to NAs if simplified to vector.

**Examples**

```
x <- msgpack_format(1:10)
x_packed <- msgpack_pack(x)
x_unpacked <- msgpack_unpack(x_packed)
x_simplified <- msgpack_simplify(x_unpacked)
```

---

```
msgpack_timestamp_decode
      'MsgPack' Timestamp
```

---

**Description**

Decodes a timestamp from the 'MsgPack' extension specifications.

**Usage**

```
msgpack_timestamp_decode(x, posix = T, tz = "UTC")

msgpackTimestampDecode(x, posix = T, tz = "UTC")
```

**Arguments**

x	A raw vector with attribute EXT = -1, following the 'MsgPack' timestamp specifications.
posix	Return a POSIXct object. Otherwise, return a list with seconds and nanoseconds since 1970-01-01 00:00:00.
tz	If returning a POSIXct, set the timezone. Note that this doesn't change the underlying value.

**Value**

A POSIXct or list. `mt <- Sys.time() attr(mt, "tzone") <- "UTC" mp <- msgpack_pack(msgpack_timestamp_encode(mt)) mtu <- msgpack_timestamp_decode(msgpack_unpack(mp)) identical(mt, mtu)`

---

```
msgpack_timestamp_encode
      'MsgPack' Timestamp
```

---

### Description

Encodes a timestamp to the 'MsgPack' specifications.

### Usage

```
msgpack_timestamp_encode(posix = NULL, seconds = NULL, nanoseconds = NULL)
```

```
msgpackTimestampEncode(posix = NULL, seconds = NULL, nanoseconds = NULL)
```

### Arguments

posix	A POSIXct or POSIXlt or anything that can be coerced to a numeric.
seconds	The number of seconds since 1970-01-01 00:00:00 UTC. Can be negative. Don't use seconds and nanoseconds if you use posix (and vice versa).
nanoseconds	The number of nanoseconds since 1970-01-01 00:00:00 UTC. Must be less than 1,000,000,000 and greater than 0.

### Value

A serialized timestamp that can be used as input to msgpack\_pack. Briefly, this is an extension type -1 that is variable length, depending on the desired range and precision.

### Examples

```
mt <- Sys.time()
attr(mt, "tzone") <- "UTC"
mp <- msgpack_pack(msgpack_timestamp_encode(mt))
mtu <- msgpack_timestamp_decode(msgpack_unpack(mp))
identical(mt, mtu)
```

---

```
msgpack_unpack      'MsgPack' Unpack
```

---

### Description

De-serialize a 'MsgPack' message. Array is converted into List. Map is converted into Map/Data.frame. Extension types are converted into raw vectors with EXT attribute. Integers, Floats, Strings, Raw and Nil are converted into Integer, Float, Character, Raw and NULL respectively.



**Usage**

```
msgpack_unpack(message, simplify = F)
```

```
msgpackUnpack(message, simplify = F)
```

**Arguments**

message	A raw vector containing the message.
simplify	Default false. Should the return object be simplified? This is generally faster and more memory efficient.

**Value**

The message pack object(s) converted into R types. If more than one object exists in the message, a list of class "msgpack\_set" containing the objects is returned.

**See Also**

See examples/tests.r for more examples.

**Examples**

```
x <- msgpack_format(1:10)
x_packed <- msgpack_pack(x)
x_unpacked <- msgpack_unpack(x_packed)
x_simplified <- msgpack_simplify(x_unpacked)
```

---

msgpack_write	<i>'MsgPack' write</i>
---------------	------------------------

---

**Description**

A helper function to serialize an object and write it to a file, or a connection.

**Usage**

```
msgpack_write(..., msg = NULL, file, mode = "auto")
```

```
msgpackWrite(..., msg = NULL, file, mode = "auto")
```

**Arguments**

...	Serializable R objects.
msg	Message to write to file. If not NULL and a raw vector, write it instead of the R objects. Default: NULL.
file	A connection, or a string describing the file or pipe to write to, depending on the mode.
mode	One of "auto", "file", "gzip" or "pipe". If "auto", detects based on the file string (any space == pipe, ".gz" == gzip, file otherwise). Ignored if file is a connection.

**Examples**

```
tmp <- tempfile(fileext=".gz")
msgpack_write(1:10, file=tmp)
x <- msgpack_read(tmp, simplify=TRUE)
```

# Index

## \* **package**

RcppMsgPack-package, [2](#)

arrayEx, [3](#)

enumEx, [3](#)

msgpack\_format, [4](#)

msgpack\_map, [4](#)

msgpack\_pack, [5](#)

msgpack\_read, [6](#)

msgpack\_simplify, [6](#)

msgpack\_timestamp\_decode, [7](#)

msgpack\_timestamp\_encode, [8](#)

msgpack\_unpack, [8](#)

msgpack\_write, [9](#)

msgpackFormat (msgpack\_format), [4](#)

msgpackMap (msgpack\_map), [4](#)

msgpackPack (msgpack\_pack), [5](#)

msgpackRead (msgpack\_read), [6](#)

msgpackSimplify (msgpack\_simplify), [6](#)

msgpackTimestampDecode  
(msgpack\_timestamp\_decode), [7](#)

msgpackTimestampEncode  
(msgpack\_timestamp\_encode), [8](#)

msgpackUnpack (msgpack\_unpack), [8](#)

msgpackWrite (msgpack\_write), [9](#)

RcppMsgPack (RcppMsgPack-package), [2](#)

RcppMsgPack-package, [2](#)