

Package: littler (via r-universe)

September 24, 2024

Type Package

Title R at the Command-Line via 'r'

Version 0.3.20.1

Date 2024-05-03

Author Dirk Eddelbuettel and Jeff Horner (2006-2008)

Maintainer Dirk Eddelbuettel <edd@debian.org>

Description A scripting and command-line front-end is provided by 'r' (aka 'littler') as a lightweight binary wrapper around the GNU R language and environment for statistical computing and graphics. While R can be used in batch mode, the r binary adds full support for both 'shebang'-style scripting (i.e. using a hash-mark-exclamation-path expression as the first line in scripts) as well as command-line use in standard Unix pipelines. In other words, r provides the R language without the environment.

URL <https://github.com/eddelbuettel/littler>,
<https://dirk.eddelbuettel.com/code/littler.html>,
<https://eddelbuettel.github.io/littler/>

BugReports <https://github.com/eddelbuettel/littler/issues>

License GPL (>= 2)

OS_type unix

SystemRequirements libR

Suggests simplermardown, docopt, rcmdcheck, whoami

VignetteBuilder simplermardown

RoxygenNote 5.0.1

Repository <https://eddelbuettel.r-universe.dev>

RemoteUrl <https://github.com/eddelbuettel/littler>

RemoteRef HEAD

RemoteSha b1b3b14caabd38ed0ac827b37f05cbcd8ec3b23c

Contents

littler	2
r	3
Index	4

littler	<i>Command-line and scripting front-end for R</i>
---------	---

Description

The *r* *binary* provides a convenient and powerful front-end. By embedding R, it permits four distinct ways to leverage the power of R at the shell prompt: scripting, filename execution, piping and direct expression evaluation.

Details

The *r* front-end was written with four distinct usage modes in mind.

First, it allow to write so-called ‘shebang’ scripts starting with `#!/usr/bin/env r`. These ‘shebang’ scripts are perfectly suited for automation and execution via e.g. via cron.

Second, we can use `r somefile.R` to quickly execute the name R source file. This is useful as *r* is both easy to type—and quicker to start that either R itself, or its scripting tool *Rscript*, while still loading the *methods* package.

Third, *r* can be used in ‘pipes’ which are very common in Unix. A simple and trivial example is `echo 'cat(2+2)' | r` illustrating that the standard output of one program can be used as the standard input of another program.

Fourth, *r* can be used as a calculator by supplying expressions after the `-e` or `--eval` options.

Value

Common with other shell tools and programs, *r* returns its exit code where a value of zero indicates success.

Note

On OS X one may have to link the binary to, say, `lr` instead. As OS X insists that files named *R* and *r* are the same, we cannot use the latter.

Author(s)

Jeff Horner and Dirk Eddelbuettel wrote *littler* from 2006 to today, with contributions from several others.

Dirk Eddelbuettel <edd@debian.org> is the maintainer.

Examples

```
## Not run:
#!/usr/bin/env r          ## for use in scripts

other input | r          ## for use in pipes

r somefile.R             ## for running files

r -e 'expr'              ## for evaluating expressions

r --help                 ## to show a quick synopsis

## End(Not run)
```

r

Return Path to r Binary

Description

Return the path of the install r binary.

Usage

```
r(usecat = FALSE)
```

Arguments

usecat Optional toggle to request output to stdout (useful in Makefiles)

Details

The test for Windows is of course superfluous as we have no binary for Windows. Maybe one day...

Value

The path is returned as character variable. If the usecat option is set the character variable is displayed via `cat` instead.

Author(s)

Dirk Eddelbuettel

Index

* **package**
 littler, [2](#)

cat, [3](#)

littler, [2](#)

r, [3](#)