

# Package: pkgKitten (via r-universe)

August 30, 2024

**Type** Package

**Title** Create Simple Packages Which Do not Upset R Package Checks

**Version** 0.2.4

**Date** 2024-08-30

**Description** Provides a function `kitten()` which creates cute little packages which pass R package checks. This sets it apart from `package.skeleton()` which it calls, and which leaves imperfect files behind. As this is not exactly helpful for beginners, `kitten()` offers an alternative. Unit test support can be added via the 'tinytest' package (if present), and documentation-creation support can be added via 'roxygen2' (if present).

**License** GPL (>= 2)

**Suggests** whoami (>= 1.1.0), tinytest, roxygen2

**URL** <https://github.com/eddelbuettel/pkgkitten>,  
<https://eddelbuettel.github.io/pkgkitten/>

**BugReports** <https://github.com/eddelbuettel/pkgkitten/issues>

**RoxygenNote** 6.0.1

**Repository** <https://eddelbuettel.r-universe.dev>

**RemoteUrl** <https://github.com/eddelbuettel/pkgkitten>

**RemoteRef** HEAD

**RemoteSha** 9db2d93b13de2fbc4fc434dcf859612f7e039096

## Contents

pkgKitten-package	2
kitten	2
playWithPerPackageHelpPage	3
Index	5

---

pkgKitten-package	Create simple packages using the kitten function.
-------------------	---

---

### Description

The base R function `package.skeleton()` is very helpful, but insist on creating packages which do not pass R CMD check.

That is silly,

This package helps with this issue. No more, no less.

### Author(s)

Dirk Eddelbuettel wrote the package and maintains it.

### See Also

[package.skeleton](#), the ‘Writing R Extensions’ manual.

---

kitten	Create a very simple package
--------	------------------------------

---

### Description

The kitten function creates an (almost) empty example package.

### Usage

```
kitten(name = "anRpackage", path = ".", author, maintainer, email,
       license = "GPL (>= 2)", puppy = TRUE, bunny = TRUE)
```

### Arguments

name	The name of the package to be created, defaults to “anPackage”
path	The path to the location where the package is to be created, defaults to the current directory.
author	The name of the author, defaults to the result of <a href="#">fullname</a> (or “Your Name” as fallback).
maintainer	The name of the maintainer, also defaults to <a href="#">fullname</a> or author if the latter is given.
email	The maintainer email address, defaults to <a href="#">email_address</a> (or “your@email.com” as fallback).
license	The license of the new package, defaults to “GPL-2”.
puppy	Toggle whether <code>tinytest::puppy</code> add unit testing, default to true (but conditional on <code>tinytest</code> being installed).
bunny	Toggle whether <code>roxygen2</code> should be used for the the creation of Rd files from R, default is true (but also conditional on <code>roxygen2</code> being install).

## Details

The `kitten` function can be used to initialize a simple package. It is created with the minimal number of files. What distinguished it from the function `package.skeleton()` in base R (which it actually calls) is that the resulting package passes R CMD check cleanly.

Because every time you create a new package which does *not* pass R CMD check, a kitten experiences an existential trauma. Just think about the kittens.

## Value

Nothing is returned as the function is invoked for its side effect of creating a new package.

## Author(s)

Dirk Eddelbuettel

---

`playWithPerPackageHelpPage`

*Create a very simple package help page*

---

## Description

The `playWithPerPackageHelpPage` function creates an basic package help page.

## Usage

```
playWithPerPackageHelpPage(name = "anRpackage", path = ".",  
  maintainer = "Your Name", email = "your@email.com")
```

## Arguments

<code>name</code>	The name of the package to be created, defaults to “anRpackage”
<code>path</code>	The path to the location where the package is to be created, defaults to the current directory.
<code>maintainer</code>	The name of the maintainer, defaults to “Your Name” or author if the latter is given.
<code>email</code>	The maintainer email address.

## Details

The `playWithPerPackageHelpPage` function can be used to create a simple help page for a package.

It has been split off from the `kitten` function so that it can be called from other packages. As such, it is also exported from **pkgKitten**.

**Value**

Nothing is returned as the function is invoked for its side effect of creating a new package.

**Author(s)**

Dirk Eddelbuettel

# Index

## \* **package**

pkgKitten-package, [2](#)

email\_address, [2](#)

fullname, [2](#)

kitten, [2](#)

package.skeleton, [2](#)

pkgKitten (pkgKitten-package), [2](#)

pkgKitten-package, [2](#)

playWithPerPackageHelpPage, [3](#)